CLAIM AMENDMENTS

Claim Amendment Summary

Claims pending

- At time of the Action: Claims 1-14.

- After this Response: Claims 1-14.

Canceled or Withdrawn claims: none.

Amended claims: none.

New claims: none.

Claims:

1.   (PREVIOUSLY PRESENTED) A   multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job from multiple sources on the MFD

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy job from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job and that includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to the MFD.

SERIAL NO.: 09/728,097
ATTY DOCKET NO.: 10001448
RESPONSE TO OFFICE ACTION DATED

2

01310410005 G:\HPDJ27us\HP1-127us.m03.doc

PAGE 4/18 * RCVD AT 3/31/2004 3:58:13 PM (Eastern Standard Time) * SVR:USPTO-EFXRF-1/0 * DNIS:3729306 * CSID:509 323 8979 * DURATION (mm-ss):04-30

2.   (PREVIOUSLY PRESENTED) A Mopy-enabled multifunction device (MFD) comprising:

a printing engine;

multiple sources;

multiple destinations;

a receiver configured to receive a Mopy job from multiple-original-output ("Mopying") control system for use with the MFD, the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to the MFD.

SERIAL NO.: 09/728,097
ATTY DOCKET NO.: 10001448
RESPONSE TO OFFICE ACTION DATED

3

PAGE 5/18 * RCVD AT 3/31/2004 3:58:13 PM [Eastern Standard Time] * SVR:USPTO-EFXRF-1/0 * DNIS:8729306 * CSID:509 323 8979 * DURATION (mm-ss):04-30

3.   (PREVIOUSLY PRESENTED) A printer driver comprising a multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to the MFD..

4.   (PREVIOUSLY PRESENTED) An application comprising a multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to the MFD..

SERIAL NO.: 09/728,097
ATTY DOCKET NO.: 10001448   4
RESPONSE TO OFFICE ACTION DATED

PAGE 6/18 * RCVD AT 3/31/2004 3:58:13 PM [Eastern Standard Time] * SVR:USPTO-EFXRF-1/0 * DNIS:3729306 * CSID:509 323 8979 * DURATION (mm-ss):04-30

5.   **(PREVIOUSLY PRESENTED)** An   operating   system comprising a multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to the MFD..

6.   **(PREVIOUSLY PRESENTED)** A method facilitating multiple-original-output ("Mopying") control of a Mopy-enabled multifunction device (MFD), the method comprising:

specifying a source for a Mopy in a Mopy job from multiple sources on the MFD;

specifying a destination for a Mopy in a Mopy job from multiple destinations on the MFD.

5

7.   **(PREVIOUSLY PRESENTED)** A method as recited in claim 6, further comprising:

formatting a Mopy job, such job includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

transmitting the Mopy job to the MFD.

8.   **(PRESENTLY AMENDED)**   A computer-readable medium having computer-executable instructions that, when executed by a computer, performs a method comprising:.

specifying a source for a Mopy in a Mopy job from multiple sources on a Mopy-enabled multifunction device (MFD);

specifying a destination for a Mopy in a Mopy job from multiple destinations on the MFD.

9.   **(PREVIOUSLY PRESENTED)** A   multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection specifier configured to select a source for each Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection specifier configured to select a destination for each Mopy in a Mopy job from multiple destinations on the MFD.

10. (PREVIOUSLY PRESENTED) A system as recited claim 9, further comprising:

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for each Mopy in the job and destination-selecting directions for each Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to the MFD.

11. (PREVIOUSLY PRESENTED) A Mopy-enabled multifunction device comprising:

a printing engine;

multiple sources;

multiple destinations;

a receiver configured to receive a Mopy job from multiple-original-output ("Mopying") control system for use with a MFD, the system comprising:

a source-selection specifier configured to select a source for each Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection specifier configured to select a destination for each Mopy in a Mopy job from multiple destinations on the MFD.

SERIAL NO.: 09/728,097
ATTY DOCKET NO.: 10001448
RESPONSE TO OFFICE ACTION DATED

7

033104100S G:\UIP1\127\HP1-127al-801.doc

PAGE 9/18 * RCVD AT 3/31/2004 3:58:13 PM [Eastern Standard Time] * SVR:USPTO-EFXRF-1/0 * DNIS:8729306 * CSID:509 323 8979 * DURATION (mm-ss):04-30

12. **(PREVIOUSLY PRESENTED)** A printer driver comprising a multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising.

a source-selection specifier configured to select a source for each Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection specifier configured to select a destination for each Mopy in a Mopy job from multiple destinations on the MFD.

13. **(PREVIOUSLY PRESENTED)** An application comprising a multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising.

a source-selection specifier configured to select a source for each Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection specifier configured to select a destination for each Mopy in a Mopy job from multiple destinations on the MFD.

14. **(PREVIOUSLY PRESENTED)** An operating system comprising a multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising.

a source-selection specifier configured to select a source for each Mopy in a Mopy job from multiple sources on the MFD;

a destination-selection specifier configured to select a destination for each Mopy in a Mopy job from multiple destinations on the MFD.